



minipack® - torre
Packaging machines and systems

MV 70 SWING ALL.

ALUMINIUM INDUSTRIAL VACUUM - SHIFTING CHAMBER - SEALING BARS 550 MM



DESCRIPTION

The flagship feature of the **Swing line** by minipack®-torre is the sliding door of the chamber, which allows these **industrial vacuum sealer machines** to operate at high speeds. The range also includes two models at affordable prices, offering all the quality and robustness by minipack®-torre at the service of small activities.

These are the other distinctive features of the Swing industrial vacuum sealer machines:

- An analog volumetric sensor to monitor the vacuum obtained and ATM packaging
- Digital control Panel with low voltage power
- Management and storage of 10 packaging programs

All the **vacuum packaging machines** of the **Swing line** are constructed in accordance with CE regulations.

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



TECHNICAL FEATURES

Electrical power supply	V	400
Phase	ph	3
MAX power installed	kW	4,5
Dimensions of the sealing bars	mm	550
Vacuum pump	mc/h	63/100
Machine dimensions with the lid open	mm	1260x1010 h.1215
Machine dimensions with the lid closed	mm	1260x1010 h.1070
Machine weight (Net/Gross)	kg	295/330 (63m ³) 319/354 (100m ³)

minipack@-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.